



SmartBright G3 LED Floodlight

BVP151 LED240/CW PSU 200W SWB G3 GM

SmartBright G3 LED Floodlight, 24000 lm, 200 W, 865 cool daylight, 110°, Safety class I, Mounting bracket

The SmartBright G3 LED Floodlight is the new successor with robust die-cast aluminum housing suitable for general outdoor application. It delivers high efficacy and outstanding energy savings.

Product data

General Information	
Number of gear units	1 unit
Gear	-
Driver included	Yes
Light source engine type	LED
Light Technical	
Luminous Flux	24,000 lm
Luminous Efficacy (rated) (Nom)	120 lm/W
Correlated Color Temperature (Nom)	6500 K
Color rendering index (CRI)	80
Number of light sources	1
Beam angle of light source	110 degree(s)
Light source color	865 cool daylight
Optic type	Wide beam
Optical cover type	Glass
Luminaire light beam spread	110°

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Inrush current	4.38 A
Inrush time	0.0284 ms
Power Consumption	200 W
Power Factor (Fraction)	0.95
Connection	Flying leads/wires
Cable	Cable 1.0 m without plug 3-pole
Number of products on MCB of 16 A type B 11	
Temperature	
Ambient temperature range	-25 to +40 °C
Controls and Dimming	
Dimmable	No
Control interface	-

SmartBright G3 LED Floodlight

Mechanical and Housing	
Housing Material	Aluminum die-cast
Reflector material	Polycarbonate
Optic material	Glass
Optical cover material	Tempered glass
Housing Color	Grey
Mounting device	Mounting bracket
Optical cover finish	Clear
Overall length	474 mm
Overall width	336 mm
Overall height	37 mm
Effective projected area	0.112 m²
Dimensions (Height x Width x Depth)	37 x 336 x 474 mm

Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Protection class IEC	Safety class I
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	-
ENEC mark	-
Warranty period	3 years
Photobiological risk	Photobiological risk group 1 @200mm to EN62778


Photobiological risk specification	0.2 m
EU RoHS compliant	Yes

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.31, 0.34) SDCM≤5
Power consumption tolerance	+/-10%

Application Conditions	
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Not applicable

Product Data	
Order product name	BVP151 LED240/CW PSU 200W SWB G3 GM
Full product name	BVP151 LED240/CW PSU 200W SWB G3 GM
Full product code	872016973245299
Order code	911401868286
Material Nr. (12NC)	911401868286
Numerator - Quantity Per Pack	1
Net Weight (Piece)	4.660 kg
EAN/UPC - Product/Case	8720169732452
Numerator - Packs per outer box	4
EAN/UPC - Case	8720169732537

Dimensional drawing



MATELEC
SOLUTIONS & MATERIELS ELECTRIQUES

